

Installing Fonts

See the [Arch wiki on Fonts](#) for much more information. Some of this information has been copied from there for my own reference / notes.

List Installed Fonts

These commands will list installed fonts, see the subcategories below for sorting through installed fonts.

```
# List all installed fonts
fc-list

# List verbose information on a font
# Shows us font family, full-name, and postscriptname
# If this isn't grepped, we will list ALL fonts verbosely
fc-list -v | grep Weather

# List fonts for specified lang
fc-list -f '%{file}\n' :lang=ar

#+ list all japanese font families
fc-list -f "%{family}\n" :lang=ja
```

Aliases

Font aliases such as `serif`, `sans-serif`, `monospace`, and others can be used to list fonts with the below command -

```
fc-match monospace
```

Unicode Character Support

This is useful when trying to verify that the proper font is installed for displaying a unicode character.

For example, the below is matching a font for the character for a pile of poo, or `U+1F4A9` -

```
# Match unicode character with supported font
```

```
fc-match -s monospace:charset=1F4A9
```

Input this character into vim by running `:UnicodeSearch! U+1F4A9` or enter `<Ctrl><V>U1F4A9` while in insert mode within vim.

Installed by Package Manager

To list fonts installed by Pacman -

```
## list font packages installed by pacman
```

```
fc-list -f "%{file}" | xargs pacman -Qqo | sort -u
```

Manual Installation

To install fonts manually, see the `~/.local/share/fonts` directory and copy the correct font file format within. For example, to install Weather Icons simply clone the repository and copy the needed Font File to the `~/.local/share/fonts` directory.

For me, the file I needed was `weathericons-regular-webfont.ttf`, which installed the font with the full-name `Weather Icons`, seen by the output below -

```
fc-list -v | grep Weather
```

```
family: "Weather Icons"(s)
```

```
fullname: "Weather Icons Regular"(s)
```

```
postscriptname: "WeatherIcons-Regular"(s)
```

Sometimes it may be necessary to then run `fc-cache` to update the font configuration cache on our system, but generally this will be handled automatically. Nevertheless, it is a simple step to perform and ensures the font is fully recognized by our system.

If the font is not appearing in a terminal or application, ensure that the app or terminal is configured to use the newly installed font.

Misc

The below, and some of the other commands here, from user [thisoldman](#) on [Arch discussions](#) -

```
## list all fonts and styles known to fontconfig
```

```
fc-list : | sort
```

```
## list monospace fonts by family and file
```

```
fc-list -f "%{family} : %{file}\n" :spacing=100 | sort
```

```
## all bold fonts
```

```
fc-list :style=Bold | sort
```

Revision #6

Created 20 September 2019 19:45:43 by Shaun Reed

Updated 18 December 2021 16:37:39 by Shaun Reed